

- Tree branches will be trimmed or pruned to provide site lines 45.72 Meters (150 feet) back from the intersection.

SIGNAGE

- Stop or Yield signs will be installed and replaced with a minimum line of sight of 65 meters (213.25 Feet).
- All signs indicating a change of speed requires a minimum line of sight of 50 meters (164.04 Feet).
- All other signs require a minimum line of sight of 50 meters (164.04 Feet).
- Standardization for installation of signs is that signs will be mounted at a height of 2 to 3 meters (6.56 Feet to 9.84 Feet) to the bottom of the sign. At locations where pedestrian traffic is likely, the sign should be mounted at a minimum height of 2 meters or 6.56 Feet measured from the ground elevation at the base of the post to the bottom of the sign. Sign posts will be placed .61 Meters (2 feet) off the face of the curb.

All reported damaged or missing signs will be documented and repaired or replaced within a reasonable amount of time of discovery. Stop or yield signs will be repaired immediately or a temporary sign erected in its place until a new sign can be obtained.

ICE AND SNOW REMOVAL

- Snow and Ice control will be dealt with according to Policy XV-1(b) entitled Snow Removal and Clearance.

SPILLS OR LITTER

- Spills or litter reported on the road surface will be removed as required in a timely fashion.

LOOSE GRAVEL

- Oil and dust control are used as required on Town gravel roads.

PUBLIC INITIATION

- Upon public advisement of a problem area, a green sheet (Concerns and Request Form) will be filled out and the situation will be assessed immediately and acknowledged within a reasonable length of time.