

**Nu-Metrics Traffic Analyzer Study
 Computer Generated Summary Report
 City: Stettler
 Street: 50 Ave.
 Location: West of 43 St.**

A study of vehicle traffic was conducted with HI-STAR unit number 0001. The study was done in the Eastbound lane at 50 Ave. in Stettler, AB in Stettler county. The study began on Nov/08/11 at 16:48 and concluded on Nov/17/11 at 23:56, lasting a total of 223.13 hours. Traffic statistics were recorded in 60 minute time periods. The total recorded volume showed 579 vehicles passed through the location with a peak volume of 11 on Nov/15/11 at [13:48-14:48] and a minimum volume of 0 on Nov/08/11 at [22:48-23:48]. The AADT count for this study was 62.

SPEED

Chart 1 lists the values of the speed bins and the total traffic volume for each bin. At least half the vehicles were traveling in the 32 - 40 KM/H range or lower. The average speed for all classified vehicles was 37 KM/H with 9.33% vehicles exceeding the posted speed of 50 KM/H. The HI-STAR found 0.00 percent of the total vehicles were traveling in excess of 89 KM/H. The mode speed for this traffic study was 32KM/H and the 85th percentile was 45.46 KM/H.

<	16	24	32	40	48	56	64	72	80	89	97	105	113	121				
to	to	to	to	to	to	to	to	to	to	to	to	to	to	to				
15	23	31	39	47	55	63	71	79	88	96	104	112	120	>				
4	9	129	279	104	47	5	2	0	0	0	0	0	0	0				

CHART 1

CLASSIFICATION

Chart 2 lists the values of the classification bins and the total traffic volume accumulated for each bin . Most of the vehicles classified during the study were Tractor Trailers. The number of Pedestrians/Bikes in the study was 8 which represents 1 percent of the total classified vehicles. The number of Passenger Vehicles in the study was 0 which represents 0 percent of the total classified vehicles. The number of Trucks in the study was 259 which represents 45 percent of the total classified vehicles. The number of Tractor Trailers in the study was 312 which represents 54 percent of the total classified vehicles.

<	2.2	5.0	12.0															
to	to	to	to															
2.1	4.9	11.9	>															
8	0	259	312															

CHART 2

HEADWAY

During the peak traffic period, on Nov/15/11 at [13:48-14:48] the average headway between vehicles was 300 seconds. During the slowest traffic period, on Nov/08/11 at [22:48-23:48] the average headway between vehicles was 3600 seconds.

WEATHER

The roadway surface temperature over the period of the study varied between 0.00 and 0.00 degrees C. The HI-STAR determined that the roadway surface was Dry 100.00% of the time.