

**Nu-Metrics Traffic Analyzer Study
Computer Generated Summary Report**

City: Stettler

Street: 47 Ave

Location: near 48 St.

A study of vehicle traffic was conducted with HI-STAR unit number 0001. The study was done in the Westbound lane at 47 Ave in Stettler, AB in Stettler county. The study began on Sep-04-09 at 10:15 and concluded on Sep-14-09 at 09:15, lasting a total of 239.00 hours. Traffic statistics were recorded in 60 minute time periods. The total recorded volume showed 11165 vehicles passed through the location with a peak volume of 160 on Sep-12-09 at [13:15-14:15] and a minimum volume of 0 on Sep-06-09 at [05:15-06:15]. The AADT count for this study was 1,121.

SPEED

Chart 1 lists the values of the speed bins and the total traffic volume for each bin. At least half the vehicles were traveling in the 48 - 56 KM/H range or lower. The average speed for all classified vehicles was 49 KM/H with 99.10% vehicles exceeding the posted speed of 30 KM/H. The HI-STAR found 0.00 percent of the total vehicles were traveling in excess of 89 KM/H. The mode speed for this traffic study was 48KM/H and the 85th percentile was 59.56 KM/H.

< to 15	16 to 23	24 to 31	32 to 39	40 to 47	48 to 55	56 to 63	64 to 71	72 to 79	80 to 88	89 to 96	97 to 104	105 to 112	113 to 120	121 to >					
1	0	5	10	31	39	18	5	1	1	0	0	0	0	0					

CHART 1

CLASSIFICATION

Chart 2 lists the values of the classification bins and the total traffic volume accumulated for each bin.

Most of the vehicles classified during the study were Passenger Vehicles. The number of Passenger Vehicles in the study was 111 which represents 100 percent of the total classified vehicles. The number of Vans & Pickups in the study was 0 which represents 0 percent of the total classified vehicles. The number of Busses & Trucks in the study was 0 which represents 0 percent of the total classified vehicles. The number of Tractor Trailers in the study was 0 which represents 0 percent of the total classified vehicles.

< to 1.8	1.9 to 2.1	2.2 to 2.2	2.3 to 2.3	2.4 to 2.4	2.5 to 2.5	2.6 to 2.7	2.8 to 2.9	3.0 to 3.0	3.1 to 3.1	3.2 to 3.3	3.4 to 3.6	3.7 to 4.1	4.2 to 4.2	4.3 to >					
73	0	5	0	12	0	21	0	0	0	0	0	0	0	0					

CHART 2

HEADWAY

During the peak traffic period, on Sep-12-09 at [13:15-14:15] the average headway between vehicles was 22.36 seconds. During the slowest traffic period, on Sep-06-09 at [05:15-06:15] the average headway between vehicles was 3600 seconds.

WEATHER

The roadway surface temperature over the period of the study varied between 0.00 and 0.00 degrees C. The HI-STAR determined that the roadway surface was Dry 100.00% of the time.